# <del>symbol</del>'



Symbol Technologies continues its revolution of pocketable computing with the PPT 2700, combining ruggedized mobility, bar code scanning and wireless LAN connectivity with the widely popular Microsoft Palm-size PC platform. This family of data management devices now offers companies the ability to leverage the familiarity and flexibility of the Microsoft Windows® CE operating system in feature-rich pocketable computers.

#### **Enabling with Ease**

Designed to fit securely in either hand, the PPT 2700 operates by touch or pen input and allows the user to navigate applications through the familiar Windows-based environment. Buttons and triggers are positioned to ensure convenient one-handed operation in either hand. Weighing less than 12 oz/335 gm and

### PPT 2700 Series Palm-size PC's

# A Family of Rugged, Pocketable Windows® CE-based Computers

measuring only 7 in/17.8 cm high, the PPT 2700 enables users to capture, compute and communicate data from anywhere across the enterprise.

A member of the "Extreme Environments" category of Symbol products, the PPT 2700 is sealed to IP54 standards for protection against windblown rain and dust, and withstands multiple drops to concrete from up to 4 ft/1.2 m. This enables users to collect and manage data in places other Windows CE devices, like personal organizers, simply can't... at the point of activity.

Now warehouse management can conveniently use a Windows CE device rugged enough to record new inventory levels as shipments are unloaded. Or, service professionals in the field of hospitality can establish Windows-based mobile sales counters during peak times and curbside check-in at hotels — regardless of the weather!

#### Flexibility with Diverse Application

The PPT 2700 provides the standard PIM software and synchronization capabilities of a Palm-size PC and is fully compatible with standard 32-bit application development tools from Microsoft and third parties. The PPT 2700 comes with 16 MB of RAM and 12 MB of flash ROM to meet data or program storage needs. An application-programming interface (API) from Symbol allows bar code data capture and wireless communication to be easily integrated into a new or existing application.

The PPT 2700 supports Symbol's state-of-the-art miniature scan engine, the SE 900, enabling your mobile workforce to capture bar coded data even in sunlight and bright artificial light. The PPT 2740 integrates Spectrum24®, Symbol's IEEE 802.11-based wireless LAN technology for real-time data communications with your remote host system.

Now physicians and caregivers can always have access to current patient records anywhere in the hospital. Using bar code data capture and wireless LAN connectivity, the matching of data to patient is facilitated, helping to ensure the accurate dispensation of medications. Using Spectrum24 and Palm-size PC's, school administrators, teachers, and staff can now retrieve and update student records from anywhere on campus, automating paper-intensive processes such as attendance tracking and grading.

Symbol Technologies, Inc. and our Business Partners provide applicationspecific mobile computing, wireless LAN communications for voice and data, and bar code data capture solutions that allow companies the ability to gather and move information quickly, accurately and efficiently, from the point of activity to anywhere across the enterprise. To find out how your business can benefit from Symbol's innovative products, contact any of the convenient locations listed on the back panel or visit us at www.symbol.com.

## PPT 2700 Specification Highlights

Physical Characteristics		
Size:	1 in. H x 3 5/8 in. W x 7 in. L (25.4 mm x 92 mm x 177.8 mm)	
Weight (including battery):	10.3 oz / 288 gm (batch version); 11.8 oz / 330 gm (wireless version)	
Drop Specification:	4 ft / 1.2 m to concrete	
Battery:	3.7 V, 1400 mAh re-chargeable Lithium Ion	
Environmental Sealing:	IP54 (windblown dust and rain)	
Operating Temperature:	-20° to 50° C (-4° to 122° F)	
Storage Temperature:	-25° to 50° C (-13° to 122° F)	CAUTION
Humidity:	5% to 90% RH non-condensing	LASER LIGHT- DO NOT STARE INTO BEAM
Electro-Static Discharge (ESD):	8 kVdc air; 4 kVdc contact	6:30m-6:30m LASER 1.0 MELIVART MAX. OUTPUT CLASS II LASER PRODUCT
SE 900 Scan Engine:	Laser Class: CDRH Class II, IEC825-1/EN60825-1 Class I Laser Source Visible laser diode at 650 nm	
Performance Characteristics		
CPU:	NEC Vr4181 (MIPS)	
Operating System:	Windows CE 2.11	
Application Development:	Fully compatible with Microsoft API for Palm-size PC's; Symbol API available to support bar code scanning	
Display:	High contrast, anti-reflective monochrome LCD display; 1/4 VGA resolution (240 x 320 pixels)	(€
Peripherals and Accessories		
Cradles:	Vehicle, modem, single-slot serial, four-slot Ethernet	
Communication and Charging Cable:	Serial/charges battery in terminal	
Magnetic Stripe Reader (MSR):	Serial connection/swipe reader attachment	
4-Slot Universal Battery Charger (UBC):	Simultaneous charge of 1-4 batteries; Requires adapters for PPT 2700 batteries	
RF Data Communications		
Network:	Symbol Spectrum24 IEEE 802.11 airwaves standard based	
Spreading Technique:	Frequency hopping	
Data Rate:	1 Mbps	
Antenna:	Internal embedded	
Range:	Open space: up to 1000 ft./303 m;	
Typical:	180-250 ft./54-76 m	
EMI/RFI:	FCC Part 15 Class A, EMC Directive, Australian SMA	
Electrical:	Certification pending to UL 1950, CSA C22.2 No. 950, EN60950/IEC950	
Output Power:	500 mW US; 100 mW International	
Frequency Range:	Country dependent, typically 2.4 to 2.5 GHz	

Specifications are subject to change without notice. Windows \*\* is a registered trademark of Microsoft Corp. Spectrum24\*\* is a registered trademark of Symbol Technologies.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.





Part No. EP Printed in USA 9/99 ©1999 Symbol Technologies, Inc. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, Symbol Technologies, Inc.
Corporate Headquarters
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: 1-800-722-6234/1-516-738-2400
FAX: 1-516-738-5990

For Europe, Middle East and Africa Symbol Technologies EMEA Division Symbol Place, Winnersh Triangle Berkshire, England RG41 5TP TEL: 44-118-9457500 FAX: 44-118-9457500

For Asia Pacific Symbol Technologies Asia Inc. (Singapore Branch) Asia Pacific Division 230 Victoria Street #04-05 Bugis Junction Office Tower Singapore 188024 TEL: 65-337-6588/FAX: 65-337-6488 For North America and Latin America Symbol Technologies The Americas One Symbol Plaza Holtsville, NY 11742-1300 TEL: 1-800-722-6234/1-516-738-2400 FAX: 1-516-738-5990

Symbol World Wide Web Internet Site
For a complete list of Symbol subsidiaries and
Symbol Business Partners worldwide contact us at:
http://www.symbol.com
E-mail: webmaster@symbol.com

